


Finestra R32

3,5 kW

Condizionatore a finestra
Window air conditioner



	A	B	C	
	mm	mm	mm	kg
F350A5	560	400	670	43,6

CARATTERISTICHE TECNICHE

- Per installazione su finestra, case mobili, containers o tende.
- Dc Inverter

TECHNICAL FEATURES

- For installation on the window, mobile homes, containers or tends.
- DC Inverter

F350A5

Potenza frigorifera	kW	3,5	Kühlleistung
Cooling capacity	Kfrig/h	3,0	Potencia frigorífica
Puissance frigorifique	KBTU/h	12,0	Potência de refrigeração
Pot. assorbita / Power input / Puiss. absorbée	kW	1,1	Leistungsaufnahme / Pot. absorbida / Pot. absorvida
Corr. assorbita / Absorbed current / Cou. absorbé	A	5,1	Stromaufnahme / Corr. absorbida / Corr. absorvida
S.E.E.R.		5,1 - A	S.E.E.R.
Alimentazione / Power supply / Alimentation	V~, Ph, Hz	230, 1, 50	Versorgung / Alimentación / Alimentação
Portata d'aria / Air flow / Débit d'air	m³/h	683	Luftleistung / Cap. de aire / Fluxo de ar
Press. sonora / Sound pressure / Pression sonore	dB(A)	≤52	Geräuschentwicklung / Nivel de ruido / Rumorosidade
Temp. esterna / Outdoor temp. / Temp. extérieure *	°C	+17 / +43	* Außentemperatur / Temp. esterna / Temp. externa
Q.tà refrigerante / Refrigerant q.ty / Q. frigorifère	R32 / g	480	Kältemittel / C. refrigerante / Q. refrigerante

* Limiti di funzionamento / Operating limits / Limites de fonctionnement / Betriebs-Grenzwerte / Limites de funcionamiento / Limites de funcionamento
 Condizioni di prova raffreddamento: int. 27°C b.s. / 19,5°C b.u. - est. 35°C b.s. / Cooling test conditions: in 27°C d.b. / 19,5°C w.b. - out 35°C d.b. / 24°C w.b.
 Conditions d'essai refroidissement: int. 27°C b.s. / 19,5°C b.u. - ext. 35°C b.s. / Prüfbedingungen Kühlung: in 27°C d.b. / 19,5°C w.b. - out 35°C d.b. / 24°C w.b.
 Condiciones de prueba refrigeración: int. 27°C b.s. / 19,5°C b.u. - ext. 35°C b.s. / Condições de prova arrefecimento: int. 27°C d.b. / 19,5°C w.b. - ext. 35°C d.b. / 24°C w.b.

